

DDN-540C

Professional High Resolution Color Day/Night Camera



Features:

- Provides crystal clear image at low illumination (0.003 Lux)
- Day/Night auto switching
- SONY 1/3" Super HAD CCD Sensor
- High resolution at 540 TVL
- Built-in Digital Noise Reduction (DNR) function
- Built-in OSD setup menu with 5 push buttons
- Built-in RS-232 port for remote control
- Built-in 4 programmable zone On/Off privacy function
- Lens and bracket not included

Specifications:

| | |
|-------------------------------|---|
| Image Inductor | SONY 1/3" Super HAD CCD Sensor |
| Resolution | 811(H) x 508(V) (410,000 pixels) |
| Horizontal | 540 TVL |
| Maximum Aperture Ratio | 1 : 1.3 ~ 2.0 |
| Scan System | 2 : 1 Interlaced |
| Synchronization | Internal / Line Lock selectable |
| Electronic Shutter Speed | 1/60 ~ 1/120,000 sec |
| Gain Control | AGC-L, AGC-H, OFF selectable |
| Sense-Up | Auto/Off selectable |
| White Balance | W-ATW / S-ATW / AWC / Manual selectable |
| Min. Illumination | 0.003 Lux (Sense-up) / 0.3 Lux (F1.3) |
| S/N (Y Signal) | 50 dB (Weight On) |
| Digital Noise Reduction (DNR) | On / Low / Middle / High selectable |
| Motion Detection | On / Off selectable |
| On Screen Display (OSD) Menu | Built-in |
| Privacy Function | On / Off (4 Programmable zoon) |
| Video Output | Composite Video 1.0 Vp-p 75 Ohm |
| Operation Temperature | 14° ~ 122° F |
| Operation Humidity | 30% ~ 90 % RH |
| Lens Type | C / CS Mount Lens |
| Power Supply | DC 12 V |
| Power Consumption | 3.36W (280 mA) |

Matco, Inc.

649 S. Vermont St.
 Palatine, IL 60067
 U.S.A.
 Phone: (847) 202-0010
 Fax: (847) 202-0018
 Email: EverSecure@matco.com
www.matco.com