

DX-VP-520W

Weather/Vandal Proof Color IP Dome Camera



Features:

- Directly accessible via any network connected
- Built-in video web server
- Built-in 32 bit RISC CPU
- Built-in 128-256 MB RAM
- Above 32M/64M, 32 bit color MS VGA
- Embedded Linux RTOS
- Built-in TCP/IP, HTTP, ARP, PARP, ICMP, DHCP, SMTP network protocol. & Pelco-P communication protocol
- RJ45, RS-232/485 interface
- MPEG-4 video compression format
- 30 frames/sec transmission rate
- 3 level password protection
- SONY 1/4" Super HAD CCD sensor
- 420 TVL
- 0.8 Lux. Minimum illumination
- Weather proof (IP55) & vandal proof

Specifications:

Image Inductor	SONY 1/4" Super HAD CCD Sensor
Resolution	D1: 720(H) x 576(V); CIF: 352(H) x 288(V); QCIF: 176(H) x 144(V)
Horizontal	420 TVL
S/N Ratio	More than 48 dB
Compression Format	MPEG-4
Max. Frame Rate	30 frames/sec
CPU	Built-in 32 bit RISC Processor (Intel/AMD 1.2G/2.0GHz or above)
Memory	Above 128-256M
VGA	Above 32M/64M, 32 bit color MS
OS	Embedded Linux RTOS
RAM/ROM	64MB/8MB
Network Protocol	TCP/IP, HTTP, ARP, PARP, ICMP, DHCP, SMTP, etc.
Network Port	RJ45
Network Browser	IE5.0 or above
Lens	3.6, 6.0, 8.0 mm Lens
PTZ Control	Built-in Pelco-P protocol, RS232/485 port
Video Output	Composite Video 1.0 Vp-p 75 Ohm
Operation Temperature	23° ~ 113° F
Operation Humidity	< 85 % RH
Power Supply	DC 12 V (<=5W)
Dimension	Ø155 x 96mm

Matco, Inc.

649 S. Vermont St.
 Palatine, IL 60067
 U.S.A.

Phone: (847) 202-0010
 Fax: (847) 202-0018
 Email: EverSecure@matco.com
www.matco.com